

- · Use with roll roofing
- · Great adhesive & bonding strength
- Adds extra waterproof protection
- Fiber reinforced
- Heavy brush grade

DESCRIPTION: Gardner[®] Roll Roofing Adhesive is a liquid applied, brushable, asphalt based adhesive, designed to bond sheets roll roofing and also adds additional waterproofing protection to the roof surface. No Heating Needed.

WHAT IS NEEDED TO COMPLETE THE JOB? Brush, gloves and roll roofing material.

PREPARATION: Surfaces must be clean, free of surface rust and loose material. Apply on a clear warm day with no rain forecasted for 24-36 hours. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECTLY TO HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50° and 120°F. In colder weather (50°F and below), product should be stored in heated room (70° to 80°F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round.

APPLICATION: Use brush to spread across surface of roof and roll the rolls of roofing material into wet adhesive.

PRECAUTIONS: Apply in exterior applications only. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100° F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use. Don't apply to wet or damp surfaces. Do not use on EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first.

COVERAGE RATE: Covers approx. 40 - 45 sq. ft. per gallon.

HOW TO CLEAN-UP: Clean tools with mineral spirits or paint thinner.

ROLL ROOFING ADHESIVE Data Sheet

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, Ibs.	8.0-8.2 lbs.
Residue by Evaporation, %	70 min.
Combustible Solvents	Mineral Spirits
Consistency	Brush
Cure Time (at recommended coverages)	4-8 hours to set
	7-14 days full cure
	(depending on bonding surface)
Application Temperatures	50°-120°F
Flammability (Flash point, °F solvent)	105°F
Clean-up Tools	Mineral Spirits, Kerosene

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	8.5 lbs.
(6) gallon containers/case	50 lbs.
5 gallons (18.9L)	45 lbs.
55 gallons (208.2L)	485 lbs.

CAUTION!: HARMFUL OR FATAL IF SWALLOWED. USE WITH ADEQUATE VENTILATION. FOR EXTERIOR USE ONLY. KEEP OUT OF REACH OF CHILDREN.

Contains petroleum based products. Keep away from heat, sparks and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, wash with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention, immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vorniting. Call physician immediately.

CALIF. PROP. 65. • **CHEMICAL WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS: 250 g/L max. (2.07 lbs./gal.)

COMPLIANCE: SCAQMD RULE #1168

ASPHALT MINERAL SPIRITS CELLULOSE FIBER Product is asbestos free PATENT PENDING C.A.S.# 8052-42-4 C.A.S.# 8052-41-3 C.A.S.# 65996-61-4

WARRANTY AND DISCLAIMER:

Gardner-Gibson, Inc. warranties this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449 Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com