



3019-1-61

SILICONIZED ACRYLIC LATEX CAULK Data Sheet

DYNAMITE® 3000 SILICONIZED ACRYLIC CAULK

- Interior/Exterior
- General Use
- Paintable
- Non-Drip Plunger

Dynamite® 3000 is a siliconized acrylic latex caulk designed for general purpose sealing for interior or exterior applications. Use for caulking areas with no movement that will be painted over. Product is designed to be painted over.

Dynamite 3000 may be applied on wood, brick, concrete, plaster, masonry, metal and dry-wall. It provides a reliable seal for seams around doors, paneling, windows, woodwork, baseboards and many other household surfaces.

Why use Dynamite 3000?

- Good Adhesive Qualities
- Paintable When Cured
- Meets ASTM C-834
- Easy Water Clean Up

How do I apply Dynamite 3000?

1. Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease, oil and mildew. Apply the caulk when surfaces are clean and dry, and both the surface and the air temperatures are above 40° F.

2. Trim nozzle to the desired bead size and load in caulk gun. While applying caulk, hold nozzle at a 45° angle, pushing caulk into the gap.

3. Caulk may be smoothed with a wet finger, sponge or brush.

Important: When smoothing caulk, the remaining bead must be no smaller than 1/8" or larger than 1/2". Each 10.1 ounce cartridge covers approximately 55 linear feet per 3/16" bead.

4. Excess caulk can be cleaned up before it dries with a wet cloth. Use soap and water to clean up hands and tools.

5. Allow caulk to cure overnight before painting. For best paint results during periods of high humidity and/or cool weather, an extended curing time may be required.

6. Do not caulk if rain or freezing conditions are anticipated within 24 hours of application. Not intended for marine use, surfaces submerged in water or for repair of surface defects. Apply within one year of purchase. See the Dynamite Architectural Specification Data Sheet for detailed information.

LIMITED 40 YEAR GUARANTEE: We guarantee that if you use **Dynamite 3000 Siliconized Acrylic Caulk** as directed and it fails within 40 years of proper application, Sealant Technology will provide you with a free replacement cartridge. Return the used cartridge with your sales receipt to where the product was purchased for free replacement. This limited warranty applies for residential use only. Since it is impossible to control use and application of this product, Sealant Technology, Inc. limits its warranty and liability strictly to replacement of product proven defective. No labor costs are applicable.

ACRILICO CALAFATEA CON EL SILICÓN

- interiores y exteriores
- general uso

DYNAMITE 3000 es a siliconized el látex de acrílico calafatea diseñado para el lacre de fines generales para los usos interiores o exteriores. Uso para calafatear áreas sin el movimiento que será pintado encima. El producto se diseña para ser pintado encima.

See MSDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Meets:	ASTM C 834
Color:	White
Odor:	Mild
Consistency:	Smooth Paste
Flash Point:	Not Applicable
Vehicle:	Acrylic and Latex Polymers
Solvent:	Water
Pigments:	Calcium Carbonate and Titanium Dioxide
Dry To Touch:	30 - 60 minutes
Cure Time:	5 - 7 Days
% Solids:	80% +/- 2%
Recommended Storage Temperature:	40 F to 100 F.
Recommended Application Range:	45 F to 100 F.
Service Temperature Range:	-10 F to 150 F.
Shelf Life:	12 months

Approx. Shipping Weights: (Note: All approx. weights include container.)

12 - 10 Fl. Oz. Tubes/Case:	15 lbs.
Cases Per Pallet:	140 Cases

CAUTION! HARMFUL IF SWALLOWED. Avoid breathing vapors, use only in a well ventilated area. Avoid contact with eyes or skin. In case of contact with eyes, flush with plenty of clean, room temperature water. Seek medical attention if irritation develops. **DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN. DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40°F.** Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. For the longest life, store in controlled environment, 35°F-80°F. Do not store in direct sunlight.

VOC: less than by 1.5% wt.

INGREDIENTS:

Calcium Carbonate	1317-65-3
Acrylic Polymer	Mixture
Oxydiethylene dibenzoate	120-55-8
Mineral Spirits	8052-41-3
Ethylene Glycol	107-21-1
Titanium Dioxide	13463-67-7
and other additives.	

CALIF. PROP. 65 • CHEMICAL WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

