# **Material Safety Data Sheet**



Revision Number: 002.0 Issue date: 10/24/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI® GS-121 Gutter & Seam Sealant IDH number:

White

Product type: Sealant

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 800.624.7767

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center

Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

827681

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:pastyHEALTH:2Color:whiteFLAMMABILITY:2Odor:slightly, of solventPHYSICAL HAZARD:0

Odor: slightly, of solvent PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

WARNING: COMBUSTIBLE!

HARMFUL IF SWALLOWED OR INHALED.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Inhalation, Skin contact

**Potential Health Effects** 

Inhalation: Irritates the nose, throat and respiratory system. Abrasion of cured material such as by sanding

or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or

fatal.

**Skin contact:** Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. **Eye contact:** Contact with eyes can cause eye irritation. Symptoms may include stinging, tearing, redness,

swelling, and blurred vision.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Existing conditions aggravated by

exposure:

Eye, skin and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Limestone	1317-65-3	30 - 60	
Stoddard solvent	8052-41-3	10 - 30	
Titanium dioxide	13463-67-7	1 - 5	
1,2,4-Trimethylbenzene	95-63-6	1 - 5	
Naphthalene	91-20-3	0.1 - 1	
Quartz (SiO2)	14808-60-7	0.1 - 1	
Ethylbenzene	100-41-4	0.1 - 1	

### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If breathing is

difficult, give oxygen. If not breathing, give artificial respiration. If symptoms

develop and persist, get medical attention.

Skin contact: Rinse with running water and soap. Apply replenishing cream. Change all

contaminated clothing.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

**Ingestion:** Do not induce vomiting, seek medical advice immediately.

#### 5. FIRE FIGHTING MEASURES

Flash point: 40.56 °C (105.01 °F) no method

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: 1 %

Flammable/Explosive limits - upper: 6 %

**Extinguishing media:** Foam, dry chemical or carbon dioxide. In case of fire, keep containers cool

with water spray.

Special firefighting procedures: Wear a self-contained breathing apparatus with a full face piece operated in

pressure-demand or other positive pressure mode. Wear full protective

clothing.

Unusual fire or explosion hazards: Closed containers may explode when exposed to extreme heat. Vapors may

form explosive mixtures with air. Vapors are heavier than air and may travel

along floor to an ignition source.

Hazardous combustion products: Carbon dioxide. Carbon monoxide.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Eliminate all sources of ignition or flammables that may come into contact with

a spill of this material. Ventilate area.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Wear suitable protective clothing, gloves and eye/face protection.

## 7. HANDLING AND STORAGE

Handling: Do not pressurize, cut, heat or weld containers. Empty product containers

may contain product residue. Do not reuse empty containers. Use only in

well-ventilated areas. Keep out of the reach of children.

Storage: Keep away from heat, spark and flame. Keep containers closed when not in

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Stoddard solvent	100 ppm TWA	500 ppm (2,900 mg/m3) TWA	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
1,2,4-Trimethylbenzene	25 ppm TWA	None	None	None
Naphthalene	10 ppm TWA 15 ppm STEL (SKIN)	10 ppm (50 mg/m3) TWA	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m3) TWA	None	None

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that

follows 29 CFR 1910.134 must be followed.

Safety goggles or safety glasses with side shields. Eye/face protection:

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: pasty Color: white

IDH number: 827681

Odor: slightly, of solvent Odor threshold: Not available. pH: not applicable

10 mm hg (25 °C (77°F)) Vapor pressure:

Boiling point/range: 149 - 154 °C (300.2 - 309.2 °F) (solvent)

Not available. Melting point/ range: Specific gravity: 1.342 Vapor density: Heavier than air

40.56 °C (105.01 °F) no method Flash point:

Flammable/Explosive limits - lower: 1 % Flammable/Explosive limits - upper: 6 %

Autoignition temperature: Not available.

**Evaporation rate:** 0.08 (Butyl acetate = 1)

Solubility in water: Insoluble
Partition coefficient (n-octanol/water): Not available.

VOC content: 29 %; 388 g/l (calculated)

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition products: Carbon dioxide, carbon monoxide and irritating and/or toxic gases and

particulate may be generated by thermal decomposition or combustion.

**Incompatible materials:** Strong oxidizing agents.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Stoddard solvent	No	No	No
Titanium dioxide	No	Group 2B	No
1,2,4-Trimethylbenzene	No	No	No
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No
Ethylbenzene	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Limestone	Nuisance dust
Stoddard solvent	Irritant, Central nervous system
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity
1,2,4-Trimethylbenzene	Central nervous system, Irritant, Respiratory
Naphthalene	Blood, Central nervous system, Eyes, Irritant
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity
Ethylbenzene	Irritant, Central nervous system

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

IDH number: 827681

## 13. DISPOSAL CONSIDERATIONS

#### Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

> defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Adhesives Hazard class or division: UN 1133 Identification number: Packing group:

**Exceptions:** Consumer Commodity ORM-D (Not more than 5 L)

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives Hazard class or division: Identification number: UN 1133 Packing group:

**Exceptions:** Consumer Commodity, ID 8000, Class 9, (Not more than 5 L)

Water Transportation (IMO/IMDG)

Proper shipping name: **ADHESIVES** Hazard class or division: Identification number: **UN 1133** 

Packing group:

Exceptions: Limited quantity (Not more than 5 L).

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312:

None above reporting de minimus Immediate Health, Delayed Health, Fire

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). 1,2,4-Trimethylbenzene (CAS# 95-63-6). Naphthalene (CAS# 91-20-3).

Ethylbenzene (CAS# 100-41-4).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. WHMIS hazard class: B.3, D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.