

# XTRAFoAM<sup>®</sup>

## MINIMAL EXPANDING FOAM SEALANT

XtraFoam<sup>®</sup> is a very low expanding, one-component, closed-cell formula, multipurpose, polyurethane foam specially formulated to seal around window and door frames. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the window. It is environmentally safe, contains no CFC's or HCFC's.



## FEATURES

- Low Expansion, closed-cell formula
- Will not warp or bow frames or jambs
- Excellent stability (no shrink or post expansion)
- Very good filling capacities
- Exerts up to 90% less curing pressure than other foams
- For professional gun applications
- Provides water-resistant, airtight seal
- Excellent adhesion on most substrates
- High thermal and acoustical insulation

## APPLICATIONS

- Windows
- Doors
- Wood, Aluminum and Vinyl Doors & Windows
- Areas of Air Infiltration



## SPECIFICATIONS

Base .....	Polyurethane
Curing System .....	Moisture Cure
Core Density.....	1.25 -1.70 lbs./ cu.ft.
R-Value ASTM C518 .....	4.25 per inch
Pressure Build .....	0.15-1.20 psig
Color .....	Yellow
Service Temp.....	230 Degrees F
Curing Rate .....	30 Minutes for a 1/2 bead
Take Free.....	5 minutes for a 1/2 bead
Shelf Life .....	12 months, from date of mfg.



Proud Member

**866-512-GLUE**  
WWW.PREMIERINDUSTRIAL.NET



# XTRABOND<sup>®</sup> XTRAFoAM<sup>®</sup>

## MINIMAL EXPANDING FOAM SEALANT

### APPLICATION:

Type: ALL substrates except PE, PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing and denser cellular structure.

Method: aerosol can, shake well before use, insert into gun adaptor, turn 90 degrees where can is upside down and click to fit into foam gun. Shake can regularly during application. If PU Foam is applied in layers, spray surface with a fine water spray between each layer to ensure optimal cellular structure and perfect curing. Optimum Application temperature: 60 - 120 deg. F. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.

### USAGE:

	LINEAR FEET									
	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000	12,000	13,000
1/4" (6.3 mm)	1	2	2	2	2	3	3	4	4	4
3/8" (9.5 mm)	3	4	4	5	6	6	7	8	8	9
1/2" (12.7 mm)	5	6	7	9	10	11	12	13	14	15
	1219	1524	1829	2134	2438	2743	3048	3353	3638	3962

LINEAR METERS

### PACKAGING:


20 oz spray can. 12 cans per case.

### SHELF-LIFE:

12 months in unopened packaging in a cool and dry storage place at temperatures of 75 deg. F. Please note that XtraFoam must be stored in the upright position.

### HEALTH AND SAFETY RECOMMENDATION:

Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.



DOT 2Q

### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



866-512-GLUE  
www.xtrabond.com

REV. 8/10 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

distributed by:

